

Stainless Steel High Pressure Red Alert Filter

- Red Alert indicator signals filter element replacement to ensure efficient filtration
- Large flow capacity is ideal for large circulation and supply systems
- Integrated mounting holes make installation to frame and equipment easy
- Bottom port for installing quick flush ball valve



25M212

Technical Data

High Pressure Medium Volume Red Alert Filters	
Maximum Working Pressure	3000 psi
Flow Capacity	10 gpm
Filter Area	36 in. ²
Dimensions	4.5" width, 4.62" depth, 11.3" height
Weight	14 lb 8 oz.

Ordering Information

Part No.	Description	Inlet/ Outlet npt	Maximum WPR			Max. Delivery		Material of Construction
			psi	bar	MPa	gpm	lpm	
25M212	Red Alert Filter Assembly (no element)	3/4	3000	207	20.7	10	38	SST, glass sight and FKM o-rings
210090	Red Alert Filter Assembly with 60 mesh filter element	3/4	3000	207	20.7	10	38	SST, glass sight and FKM o-rings
210091	Red Alert Filter Assembly with 100 mesh filter element	3/4	3000	207	20.7	10	38	SST, glass sight and FKM o-rings
210092	Red Alert Filter Assembly with 200 mesh filter element	3/4	3000	207	20.7	10	38	SST, glass sight and FKM o-rings

Part No.	Description
108116	60 Mesh Filter Element
108117	100 Mesh Filter Element
108118	200 Mesh Filter Element

For more information, see manual 3A4936

All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

Call today for product information or to request a demonstration.

877.84GRACO (1-877-844-7226) or visit us at www.graco.com/finishing